

TECHNICAL SPECIFICATIONS

RETHINK INNOVATION

CACLEW	CDECIE	ICATIONS

SYSTEM SPECIFICATIONS	
Resolution	1,200 x 1,200 dpi
Paper weight	40–300 g/m² (350 g/m² optional*)
Duplex unit	Non-stack type; 40–300 g/m ²
Paper sizes	Standard:
	Min.: 182 x 139 mm
	Max.: 324 x 463 mm
	Optional:
	Min.: 95 x 139 mm*
	Max.: 324 x 483 mm**
Maximum image area	314 x 463 mm (up to 483 mm** optional)
Paper input capacity	Standard: 3,000 sheets
	Max.: 9,000 sheets
Paper output capacity	Max.: 4,200 sheets
Main unit dimensions	990 x 910 x 1,460 mm
(W x D x H)	
Main unit weight	340 kg
PRODUCTIVITY	
A4 – max. per minute	100 ppm
A3 – max. per minute	56 ppm
SRA3 – max. per minute	53 ppm
A4 – max. per hour	6,000 pph
A3 – max. per hour	3,300 pph
SRA3 – max. per hour	3,120 pph

KONICA MINOLIA CONTROLLER		
Туре	Built-in type	
Resolution	Print: 1,200 x 1,200 dpi; 600 dpi x 600 dpi Scan: 200 dpi, 300 dpi, 400 dpi, 600 dpi	
СРИ	Pentium G4400 3.3 GHz	
Memory	12 GB (DDR4 U-DIMM x2) 2,133 MHz	
HDD	1 TB (SATA/ 7,200 rpm / 3.5 inch)	
SSD	4 GB	
Interface	Ethernet 10/100/1000BASE-T; SB 3.0 host	
Page Description Language	PCL5E/XL (PCL6); Adobe PostScript 3 (PS3020); PDF directprint (PDF Ver.1.7); TIFF (TIFF Ver.6) direct print; PPML (Ver 2.2)	

SCANNER SPECIFICATIONS

SOME TENED CONTOURS	
Scan speed A4	Up to 240 opm
Scan resolution	600 x 600 dpi
Scan modes	Scan to HDD; Scan to FTP; Scan to PC; Scan to eMail;
	Scan to WebDAV; Scan to USB Memory;
	HDD to FTP/SMB/WebDAV; LDAP supported
Scan formats	TIFF; PDF; PDF(PDF/A); Encrypted PDF; XPS;
	CompactPDF; JPEG

COPIER SPECIFICATIONS

COFIER SFECII ICATIONS		
Gradations	256 gradations	
FCOT	Less than 3.4 sec. (A4 LEF)	
Magnification	25-400%, in 0.1% steps	
Mutliple copies	1–9,999	
ACCESSORIES		
Large capacity tray A4	LU-414	
Large capacity tray SRA3	LU-415	
Air assist paper feed unit	PF-709	
Stapling unit	FS-532m	
Saddle stitch kit for FS-532	SD-510	
Punch kit for FS-532	PK-525	
Post inserter for FS-532	PI-502	
Multi bypass tray	MB-507	
Output tray	OT-507	
Open stacker	OT-512	
Mount kit for 3rd party	MK-737	
Relay unit	RU-518m	
Humidification unit	HM-103	

- * With PF-709
- All specifications refer to A4-size paper of 80 g/m2 quality.
- The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.

 – The stated life expectancy of each consumable is based on specific operating conditions such as page.
- coverage for a particular page size (5 % coverage of A4).
- The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free
- All brand and product names may be registered trademarks or trademarks of their respective holders and are























Konica Minolta Business Solutions India Pvt. Ltd.

Building No: 8, Tower-C, 10th Floor, DLF Cyber City, Phase-2, Gurugram, Haryana-122002, India | Board No. +91-124-6652000 URL: www.konicaminolta.in | marcom@bin.konicaminolta.in

Connect with us : in 💟 🌠 🖸

 $Product\ appearance, configuration\ and/or\ specifications\ are\ subject\ to\ change\ without\ notice.$

This product is not available for some countries or regions.